

DIGITAL QUICK MICROMETER, ABSOLUTE ORIGIN SPEED MIC SNAP INDICATING LEVER ACTION GAGE IP65 COOLANT PROOF, BUILT IN WIRELESS TRANSMISSION

Features:

- Absolute origin
- No rotating spindle and avoiding scratch parts
- Quickly measure with super high precision lever activated - fully opens and closes in less than one second.
- Fixed thimble
- Carbide tipped spindle
- IP65 protection level
- Built in wireless transmission (blue tooth)
- Ball attachment included.
- 3V lithium battery
- Fitted case included



MD10-0001

-ABS-



Item	Range	Resolution	Accuracy	Price
MD10-0001	0-1"/0-25mm	0.00005"/0.001mm	±0.00015"/0.003mm	\$280.00/PC
MD10-0002	1-2"/25-50mm	0.00005"/0.001mm	±0.00015"/0.003mm	\$288.00/PC
MD10-0003	2-3"/50-75mm	0.00005"/0.001mm	±0.00015"/0.004mm	\$320.00/PC
MD10-0004	3-4"/75-100mm	0.00005"/0.001mm	±0.00015"/0.004mm	\$356.00/PC

ELECTRONIC DIGITAL BLADE MICROMETER

Features:

- Resolution: 0.00005"/0.001mm.
- Inch/mm conversion.
- ABS/INC switchable.
- Reset/Preset.
- Hold function for max. or min. values.
- Non-rotating spindle.
- Blade penetration=0.315".
- Blade thickness=0.03".
- Blade width=0.256".



2312-1010



Item	Range	Price
2312-1010	0-1"/0-25mm	\$189.00/PC
2312-2010	1-2"/25-50mm	\$199.00/PC
2312-3010	2-3"/50-75mm	\$209.00/PC
2312-4010	3-4"/75-100mm	\$233.00/PC
2312-5010	4-5"/100-125mm	\$246.00/PC

MULTI ANVIL MICROMETER




Features:

- Resolution: 0.0001"
- Two interchangeable anvil: flat & round.
- Carbide face on spindle
- Ratchet thimble
- Lock nut.
- Satin chrome finished.



P101-S100



Item	Range	d	Accuracy	Price
P101-S100	0-1"	0.118"(3mm)	±0.00016"	\$119.00/PC
P101-S101	1-2"	0.196"(5mm)	±0.00016"	\$142.00/PC

ELECTRONIC DIGITAL DRO SCALE UNIT, HORIZONTAL

Features:

- Max. measuring speed: 0-450mm: 1.5m/s
- 500-1000mm: 1m/s
- Manual power on/off.
- Inch/metric interchange at any position.
- Zero setting at any position.
- From 500mm with the extra functions.
- Delivery completes with mounting material.
- Power supply: 1 battery
- Can be used with 3-Axis DRO Display 0811-0301 or one Axis DRO position 1104-8111 or individually.

ABHO-0006



Item	Description	Range	Resolution	Accuracy	Price
ABHO-0006	Horizontal	0-6"/0-150mm	0.0005"/0.01mm	±0.03mm	\$72.00/PC
ABHO-0008	Horizontal	0-8"/0-200mm	0.0005"/0.01mm	±0.03mm	\$79.00/PC
ABHO-0012	Horizontal	0-12"/0-300mm	0.0005"/0.01mm	±0.04mm	\$95.00/PC
ABHO-0018	Horizontal	0-18"/0-450mm	0.0005"/0.01mm	±0.05mm	\$155.00/PC
ABHO-0024	Horizontal	0-24"/0-600mm	0.0005"/0.01mm	±0.08mm	\$189.00/PC
ABHO-0040	Horizontal	0-40"/0-1000mm	0.0005"/0.01mm	±0.10mm	\$330.00/PC

3 AXIS DRO DISPLAY UNIT (SCALE NOT INCLUDED)

Features:

- Use for long measuring of three directions, with measuring scale, vernier caliper and other digital measuring tools.
- Precision: 0.001"/0.01mm.
- Max. measuring length: 39.37"/999.99mm.
- Inch/metric conversion.
- Center-separation(1/2).
- Reset.
- Magnetic back.
- AC power supply with time delays function.
- 110V AC.

Item # 0811-0301

\$258⁰⁰
PC



ELECTRONIC DIGITAL DRO SCALE UNIT, VERTICAL

Features:

- Max. measuring speeds: 1.5m/s
- Manual power on/off.
- Inch/metric interchange at any position.
- Zero setting at any position.
- Fast tracking of minimum or maximum value during measurements.
- Delivery completes with mounting material.
- Power supply: 1 battery
- Can be used with 3-Axis DRO Display 0811-0301 or one Axis DRO position 1104-8111 or individually.



ABVE-0006



Item	Description	Range	Resolution	Accuracy	Price
ABVE-0006	Vertical	0-6"/0-150mm	0.0005"/0.01mm	±0.001"/0.02mm	\$79.00/PC
ABVE-0008	Vertical	0-8"/0-200mm	0.0005"/0.01mm	±0.0015"/0.03mm	\$94.00/PC
ABVE-0012	Vertical	0-12"/0-300mm	0.0005"/0.01mm	±0.0015"/0.03mm	\$126.00/PC
ABVE-0018	Vertical	0-20"/0-500mm	0.0005"/0.01mm	±0.002"/0.05mm	\$195.00/PC

LCD DIGITAL UNIT

Features:

- Easy to connect with a capacitive digital measuring instrument (such as digital caliper and digital indicator) to fulfill the remote and bigger display of instrument's measuring value.
- Functions as zero setting, fast tracking and normal display interchangeable, inch/mm system interchangeable can be operated directly by pressing the function button of LCD digital unit.
- Displaying value on screen of LCD digital unit will be always kept even after the power of it is shut off
- With magnet at its back, it can be placed at a position which is easy for checking.



Item # 1104-8111

\$138⁰⁰
PC

(Scale Not Included)

- Technical specifications:
Range of display: +999.99mm/39"
Resolution: 0.01mm/0.0005"
Power: 2 pieces of model LR03 basic AAA battery
Length of signal cable: 2.5m