


PRECISION TOOLMAKERS VISE

Features:

- With a v-groove jaw.
- Hardened and ground HRC 58-62.
- Square and parallel within 0.0002".
- One-piece body construction.






Item	Size	Vise Length (A)	В	н	Jaw Depth (C)	Jaw Opening (G)	F	J	Price
0235-0310	2-3/8"	6.93"	2.48"	2.48"	1.26"	0-2.87"	8.70"	2.48"	\$128.00/PC
0235-0311	3-1/2"	9.65"	3.46"	3.15"	1.57"	0-5.00"	11.57"	3.15"	\$275.00/PC
0235-0312	4"	10.04"	3.86"	3.23"	1.65"	0-4.92"	12.01"	3.23"	\$312.00/PC

PRECISION SCREWLESS VISE

Features:

- Hardened and stabilized.
- Precision ground to a mirror finish.
- Simple operation and extremely versatile.
- Squareness and parallelism are approx. ±0.0002" on critical sides.





Item	Size	Total Length (A)	В	Total Ht. (H)	С	Jaw Opening (G)	S	Price
0235-0302	2"	5.91"	1.97"	2.09"	0.98"	0-3.15"	0.20"	\$104.00/PC
0235-0303	3"	7.48"	2.87"	2.76"	1.38"	0-3.94"	0.24"	\$132.00/PC
0235-0304	4"	9.65"	3.94"	3.54"	1.77"	0-5.12"	0.31"	\$278.00/PC

Sq. & Parallel

0.0002"

0.0003'

0000000

MAX

PRECISION SCREWLESS SINE VISE

Features:

- Provides quick and accurate means of holding a workpiece at an angle for machining, drilling and grinding.
- Accuracy is further enhanced by the fact that the center, distance between the holes is held within 0.0002.

Center Distance

5.000" within 0.0002"

10.000" within 0.0002'

- Small angles can be set easily and accurately by using standard gage block sets because of the built-in 0.200" minute steps.
- · Made of hardened solid steel.
- All surfaces hardened and ground.
- Adjusts: 0-45°

BA66-0420

BA66-0425

Jaw Cap

BA66-0420		
Capacity	Jaw Height	Price
0-3.94"	1.38"	\$269.00/PC

PRECISION SCREWLESS VISE

7.48" x 2.87" x 4.13"

11" x 4" x 4-5/8"

- Features:

 Produced of high-quality steel, carburized to surface hardness: HRC 55-60.

 Parallelism 0.003mm/100mm, squareness 0.005mm/100mm.

 Quickly clamping and easy operation.

 Used for precision measurement and inspection precision grinding, EDM and wire-cutting machine.

 Guarantee high accuracy at any position.

 Material: 20 CrMnTi.

- Movable jaw pulls into base at 45 to 60° to ensure maximum holding power and hold down force, eliminating tilting and lifting

 Strong fitted box.

It	em	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)	G (mm)	-1	J (mm)	K (mm)	Weight (kg)	Price
0536	6-VB25	175	63	63	32	31	35	0-90	M6	11	11	2.9	\$126.00/PC
	6-VB30	190	73	70	35	35	35	0-100	M6	12	12	4.3	\$136.00/PC
0536	6-VB35	235	88	80	40	40	40	0-130	M8	14	14	6.5	\$249.00/PC



\$580.00/PC

PRECISION TOOLMAKERS VISE

Features:

- Produced of high-quality steel, carburized to surface hardness: HRC 55-60.
- Parallelism 0.003mm/100mm, squareness 0.005mm/100mm.
- Quick clamping and easy operation.
 Used for precision measurement and inspection precision
- grinding, EDM and wire-cutting machine.

 Guarantee high accuracy in any position.

 Material: 20 CrMnTi.
- Has a ground "V" way, detachable replacement jaws.

	• Strong litted	Strong littled box.													
	Item	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)	G (mm)	H (mm)	I	J (mm)	K (mm)	(mm)	Weight (kg)	Price
ı	0536-VS20	156	48	52	25	27	25	0-63	34	M6	8	8	125	2.3	\$126.00/PC
١	0536-VS25	176	63	63	30	33	30	0-73	40	M6	11	11	147	4.0	\$142.00/PC
	0536-VS30	190	73	73	35	38	35	0-76	45	M6	12	12	151	5.5	\$212.00/PC
l	0536-VS35	250	88	80	42	38	40	0-115	-	M8	-	-	-	10	\$299.00/PC

